

Raised and depressed lettering for cast, pressed and plastic parts

Document part number: 4 497 005 963
Technical responsibility: [shg1sh](#) C/CGB-CD
Replaces edition: 2020-03-09

Changes: Editorial editing.
Change information: [AEN 4497R34333](#) (internal document of the Bosch Group)

Area of validity, binding force, freedom to disclosure	
Valid for	Bosch Group
Binding for	No central agreement
Binding due to	No central agreement
Recommended for	Bosch Group
Disclosure	Restricted in accordance with the Guideline RB/GF 108

This Bosch-Norm is binding for suppliers if it is part of the order.

General Information			
Series		N41A Labels	
Bosch-Norm standardization expert		nbu1si GS/TED	
Document language		en	
Original Language		en	
Translation			
Release date	Source language	Target language	Translated by
2026-01-19	de	en	GS/TED

In case of doubt the original language edition of this Bosch-Norm applies.
The comma is used as the decimal marker.
Valid issue only in NormMaster. No change service for copies.

Table of Contents

1	Scope	2
2	Introduction	2
3	Pressed metal parts	3
4	Pressure diecasting, permanent mold casting, plastics	4
5	Sand casting	5
6	Normative references	6

1 Scope

This Bosch-Norm specifies guidelines that are mandatory for the labeling of any product of the Bosch Group.
Labeling rules for products see [N41A A1](#).

2 Introduction

All details in product labeling are based on the font "Bosch Sans", except for the Bosch symbol and logotype. This font family is exclusively designed for Bosch, it can be downloaded from the Bosch Bosch Brand Guide ([brandguide.bosch.com](#)) (see [N41A F1](#) and [N41A F4/1](#)).

The specified sizes are empirical values for the various manufacturing methods treated here. A distinction is made between font size h₁ (see figure 1) and raised font or depressed font. h₂ (see figure 2)


Figure 1: Font size h₁=cap height of capital letters




3 Pressed metal parts

Prefer the raised font for pressed parts of aluminum and other metals. Use the depressed font only if it cannot be avoided due to production-related reasons. Use the font Bosch Sans Engraving for depressed purposes. For raised fonts use Bosch Sans regular.

Figure 2: Raised and depressed fonts for pressed parts



Raised font
Designation: B1/1/..



Depressed font
Designation: B1/2/..

Table 1: Designation of raised fonts for pressed parts

Designation	h_1 [mm]	h_2 [mm]	r [mm]
B1/1/3	3	0,3	0,2
B1/1/4	4	0,4	0,3
B1/1/5	5	0,5	0,35
B1/1/6	6	0,6	0,45
B1/1/8	8	0,8	0,6
B1/1/10	10	1	0,6
B1/1/12,5	12,5	1,25	0,6
B1/1/16	16	1,6	0,6

Table 2: Designation of depressed fonts for pressed parts


Designation	h_1 [mm]	h_2 [mm]	r [mm]	b [mm]
B1/2/3	3	0,3	0,05	0,2
B1/2/4	4	0,3	0,1	0,3
B1/2/5	5	0,4	0,1	0,4
B1/2/6	6	0,4	0,1	0,4
B1/2/8	8	0,6	0,2	0,6
B1/2/10	10	0,8	0,2	0,8
B1/2/12,5	12,5	1	0,3	1
B1/2/16	16	1,2	0,4	1,2

4 Pressure diecasting, permanent mold casting, plastics


Prefer the raised font for products manufactured by pressure diecasting or permanent mold casting, and for plastic parts. Use the depressed font only if it cannot be avoided due to production-related reasons.

The font size h_1 (see figure 1) used for permanent mold casting parts has to be at least 4mm.

Figure 3: Raised and depressed fonts for parts manufactured by pressure diecasting, permanent mold casting, and for plastic parts



Raised font
Designation: B1/3/..



Depressed font
Designation: B1/4/..

Table 3: Designation of raised fonts for parts manufactured by pressure diecasting, permanent mold casting, and for plastic parts

Designation	h_1 [mm]	h_2 [mm]	b [mm]
B1/3/1,6	1,6	0,1	0,1
B1/3/2	2	0,2	0,1
B1/3/2,5	2,5	0,2	0,2
B1/3/3	3	0,3	0,2
B1/3/4	4	0,4	0,3
B1/3/5	5	0,5	0,4
B1/3/6	6	0,6	0,5
B1/3/7	7	0,7	0,6
B1/3/8	8	0,8	0,7
B1/3/10	10	1	0,9
B1/3/12,5	12,5	1,2	1,1
B1/3/16	16	1,6	1,5

Table 4: Designation of depressed fonts for parts manufactured by pressure diecasting, permanent mold casting, and for plastic parts

Designation	h_1 [mm]	h_2 [mm]	b [mm]
B1/4/1,6	1,6	0,1	0,1
B1/4/2	2	0,2	0,1
B1/4/2,5	2,5	0,2	0,2
B1/4/3	3	0,3	0,2
B1/4/4	4	0,4	0,3
B1/4/5	5	0,5	0,4
B1/4/6	6	0,6	0,5
B1/4/7	7	0,7	0,6
B1/4/8	8	0,8	0,7
B1/4/10	10	1	0,9
B1/4/12,5	12,5	1,2	1,1
B1/4/16	16	1,6	1,5


BST 4497005963

TCS6FE 2026-07-01 NormMaster


5 Sand casting

Prefer depressed fonts for products manufactured by sand casting. Use the raised font only if it is unavoidable due to production-related reasons.

Figure 4: Raised and depressed fonts for sand casting parts



Raised font
Designation: B1/5/..



Depressed font
Designation: B1/6/..

Table 5: Designation of raised fonts for sand casting parts

Designation	h_1 [mm]	h_2 [mm]	b [mm]
B1/5/8	8	1	0,8
B1/5/10	10	1,2	1
B1/5/12,5	12,5	1,5	1
B1/5/15	15	1,5	1,5
B1/5/16	16	1,5	2
B1/5/20	20	2	2,5
B1/5/25	25	2	3

Table 6: Designation of depressed fonts for sand casting parts

Designation	h_1 [mm]	h_2 [mm]
B1/6/5	5	0,5
B1/6/6	6	0,6
B1/6/7	7	0,7
B1/6/8	8	0,8
B1/6/10	10	1
B1/6/12,5	12,5	1
B1/6/15	15	1,2
B1/6/16	16	1,2

Designation example: font size $h_1 = 4$ mm (raised) for pressure diecasting→ font N41A B1/3/4

BST 4497005963

TCS6FE 2026-07-01 NormMaster

6 Normative references

The following documents are necessary for using this Bosch-Norm. With dated references solely the edition referred to applies. With undated references the last edition of the indicated document applies (including all revisions). Intentionally cited historical standards are additionally identified as "H" in the column "Type".

No.	Document number (edition date)	Title	Type
1	N41A A1	Labeling rules for products and parts	Z
2	N41A A10	Use of the Bosch trademarks	Z
3	N41A F1	Product labeling, Bosch Sans for labels	Z
4	N41A F4/1	Engraving font, General	Z

Type: M = Document to be supplied; Z = Cited document; H = Historical document